

Solutions to be found on the KickDrill App



Surface BOP Exers.:	1		
Hole Section:	8,5	inch	
Surface Leak Off:	102	BAR	
LOT Mudweight used	1,2	sg	
Casing Depth MD:	2375	m	
Casing Depth TVD:	2305	m	
Measured Depth MD	3020	m	
Total Depth TVD	2802	m	
Present Mudweight:	1,3	sg	
Pumpe Input:	19,02	I/stroke	
Killrate:	30	SPM	
SCR Casing:	32	BAR	
Drillpipe Capacity:	9,08	I <mark>/m</mark>	
DP/Open Hole:	23,3	I/m	
DP/Casing	24,9	I/m	
HWDP Length:	155	m	
HWDP Capacity:	4,61	I/m	
DC Length:	140	m	
DC Capacity:	3,17	I/m	
DC/OH:	16,18	I/m	
SIDPP:	50	BAR	
SICP:	57	BAR	
PitGain	1500	liter	
Active Surf Volume:	230000	1	
RS WELLCONTROL / KICKDRILL.COM			

Surface BOP Exers.:	2		
Hole Section:	8,5	inch	
Surface Leak Off:	96	BAR	
LOT Mudweight used	1,44	sg	
Casing Depth MD:	3460	m	
Casing Depth TVD:	3460	m	
Measured Depth MD	4422	m	
Total Depth TVD	4422	m	
Present Mudweight:	1,51	sg	
Pumpe Input:	19,02	I/stroke	
Killrate:	30	SPM	
SCR Casing:	35	BAR	
Drillpipe Capacity:	9,08	I/m	
DP/Open Hole:	23,3	I/m	
DP/Casing	24	I/m	
HWDP Length:	142	m	
HWDP Capacity:	4,61	I/m	
DC Length:	140	m	
DC Capacity:	3,17	I/m	
DC/OH:	16,18	I/m	
SIDPP:	40	BAR	
SICP:	50	BAR	
PitGain	1300	liter	
Active Surf Volume:	230000	I	
RS WELLCONTROL / KICKDRILL.COM			

Surface BOP Exers.:	3		
Hole Section:	8,5	inch	
Surface Leak Off:	55	BAR	
LOT Mudweight used	1,44	sg	
Casing Depth MD:	2300	m	
Casing Depth TVD:	2300	m	
Measured Depth MD	2970	m	
Total Depth TVD	2910	m	
Present Mudweight:	1,25	sg	
Pumpe Input:	19,02	I/stroke	
Killrate:	30	SPM	
SCR Casing:	20	BAR	
Drillpipe Capacity:	9,08	I/m	
DP/Open Hole:	23,3	I/m	
DP/Casing	23,6	I/m	
HWDP Length:	110	m	
HWDP Capacity:	4,22	I/m	
DC Length:	115	m	
DC Capacity:	3,8	I/m	
DC/OH:	16,18	I/m	
SIDPP:	20	BAR	
SICP:	27	BAR	
PitGain	1400	liter	
Active Surf Volume:	230000	I	
RS WELLCONTROL / KICKDRILL.COM			

Surface BOP Exers.:	4		
Hole Section:	8,5	inch	
Surface Leak Off:	56	BAR	
LOT Mudweight used	1,44	sg	
Casing Depth MD:	2670	m	
Casing Depth TVD:	2600	m	
Measured Depth MD	3990	m	
Total Depth TVD	3850	m	
Present Mudweight:	1,42	sg	
Pumpe Input:	19,02	I/stroke	
Killrate:	30	SPM	
SCR Casing:	30	BAR	
Drillpipe Capacity:	9,08	I/m	
DP/Open Hole:	23,3	I/m	
DP/Casing	24,9	I/m	
HWDP Length:	145	m	
HWDP Capacity:	4,61	I/m	
DC Length:	140	m	
DC Capacity:	3,17	I/m	
DC/OH:	16,18	I/m	
SIDPP:	33	BAR	
SICP:	44	BAR	
PitGain	1500	liter	
Active Surf Volume:	230000	1	
RS WELLCONTROL / KICKDRILL.COM			