

## Surface BOP Exers.: 8,5 inch Hole Section: Surface Leak Off: 56 BAR LOT Mudweight used 1,69 sg Casing Depth MD: 3560 m Casing Depth TVD: 3500 m Measured Depth MD 4320 m 4255 m Total Depth TVD Present Mudweight: 1,75 sg 19,02 l/stroke Pumpe Input: Killrate: 30 SPM 50 BAR SCR Casing: Drillpipe Capacity: 9,08 I/m DP/Open Hole: 23,3 I/m DP/Casing 25,3 l/m HWDP Length: 155 m HWDP Capacity: 4,61 l/m DC Length: 132 m 3,17 l/m DC Capacity: DC/OH: 16,18 l/m SIDPP: **31** BAR SICP: 36 BAR 600 liter PitGain Active Surf Volume: 200000 |

RS WELLCONTROL / KICKDRILL.COM

## Solutions to the exersizes to be found on the KickDrill App

Surface BOP Exers.:	6		
Hole Section:	8,5	inch	
Surface Leak Off:	75	BAR	
LOT Mudweight used	1,7	sg	
Casing Depth MD:	3578	m	
Casing Depth TVD:	3420	m	
Measured Depth MD	4320	m	
Total Depth TVD	4148	m	
Present Mudweight:	1,8	sg	
Pumpe Input:	19,02	I/stroke	
Killrate:	30	SPM	
SCR Casing:	49	BAR	
Drillpipe Capacity:	9,08	I/m	
DP/Open Hole:	23,3	I/m	
DP/Casing	24,9	I/m	
HWDP Length:	162	m	
HWDP Capacity:	4,61	I/m	
DC Length:	132	m	
DC Capacity:	3,17	l/m	
DC/OH:	16,18	I/m	
SIDPP:	29	BAR	
SICP:	35	BAR	
PitGain	850	liter	
Active Surf Volume:	260000	1	
RS WELLCONTROL / KICKDRILL.COM			

Surface BOP Exers.:	7	
Hole Section:	8,5	inch
Surface Leak Off:	42	BAR
LOT Mudweight used	1,3	sg
Casing Depth MD:	1890	m
Casing Depth TVD:	1890	m
Measured Depth MD	2340	m
Total Depth TVD	2340	m
Present Mudweight:	1,39	sg
Pumpe Input:	19,02	I/stroke
Killrate:	40	SPM
SCR Casing:	36	BAR
Drillpipe Capacity:	9,08	I/m
DP/Open Hole:	23,3	I/m
DP/Casing	24,9	I/m
HWDP Length:	113	m
HWDP Capacity:	4,61	I/m
DC Length:	110	m
DC Capacity:	3,17	I/m
DC/OH:	16,18	I/m
SIDPP:	20	BAR
SICP:	25	BAR
PitGain	700	liter
Active Surf Volume:	250000	1
RS WELLCONTROL / KICKDRILL.COM		



Surface BOP Exers.:	8		
Hole Section:	8,5	inch	
Surface Leak Off:	78	BAR	
LOT Mudweight used	1,55	sg	
Casing Depth MD:	2360	m	
Casing Depth TVD:	2360	m	
Measured Depth MD	3322	m	
Total Depth TVD	3322	m	
Present Mudweight:	1,66	sg	
Pumpe Input:	19,02	I/stroke	
Killrate:	40	SPM	
SCR Casing:	45	BAR	
Drillpipe Capacity:	9,08	I/m	
DP/Open Hole:	23,3	I/m	
DP/Casing	24,9	I/m	
HWDP Length:	178	m	
HWDP Capacity:	4,61	I/m	
DC Length:	135	m	
DC Capacity:	3,17	I/m	
DC/OH:	16,18	I/m	
SIDPP:	32	BAR	
SICP:	39	BAR	
PitGain	1200	liter	
Active Surf Volume:	250000	1	
RS WELLCONTROL / KICKDRILL.COM			