

Surface BOP Exers.:	9
Hole Section:	8,5 inch
Surface Leak Off:	48 BAR
LOT Mudweight used	1,17 sg
Casing Depth MD:	1595 m
Casing Depth TVD:	1595 m
Measured Depth MD	2100 m
Total Depth TVD	2100 m
Present Mudweight:	1,27 sg
Pumpe Input:	19,02 l/stroke
Killrate:	45 SPM
SCR Casing:	34 BAR
Drillpipe Capacity:	9,08 l/m
DP/Open Hole:	23,3 l/m
DP/Casing	24,9 l/m
HWDP Length:	98 m
HWDP Capacity:	4,61 l/m
DC Length:	90 m
DC Capacity:	3,17 l/m
DC/OH:	16,18 l/m
SIDPP:	19 BAR
SICP:	23 BAR
PitGain	1100 liter
Active Surf Volume:	200000 l
RS WELLCONTROL / KICKDRILL.COM	

Solutions to the exersizes to be found on the KickDrill App



Surface BOP Exers.:	10
Hole Section:	8,5 inch
Surface Leak Off:	98 BAR
LOT Mudweight used	1,61 sg
Casing Depth MD:	3890 m
Casing Depth TVD:	3820 m
Measured Depth MD	4810 m
Total Depth TVD	4725 m
Present Mudweight:	1,75 sg
Pumpe Input:	19,02 l/stroke
Killrate:	35 SPM
SCR Casing:	64 BAR
Drillpipe Capacity:	9,08 l/m
DP/Open Hole:	23,3 l/m
DP/Casing	25,3 l/m
HWDP Length:	178 m
HWDP Capacity:	4,61 l/m
DC Length:	151 m
DC Capacity:	3,17 l/m
DC/OH:	16,18 l/m
SIDPP:	40 BAR
SICP:	44 BAR
PitGain	500 liter
Active Surf Volume:	220000 l
RS WELLCONTROL / KICKDRILL.COM	